

## OMEGA LINK OL

8130-04



|                      |                                                                                                                                                                                                                                                                                              |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Type</b>          | Lifting products                                                                                                                                                                                                                                                                             |
| <b>Material</b>      | Steel                                                                                                                                                                                                                                                                                        |
| <b>Description</b>   | <p><b>Application:</b> Link for chain, and in combination with sling hook.</p> <p><b>Material:</b> Hardened and tempered steel. Do not heat.</p> <p><b>Proof load:</b> Min. 2 x max load.</p> <p><b>Labeling:</b> Size according to the chain dimensions.</p> <p><b>Coating:</b> Yellow.</p> |
| <b>Product group</b> | 505                                                                                                                                                                                                                                                                                          |

| Part no. | Prod. Type | Dimension mm A | Dimension mm B | Dimension mm C |      |
|----------|------------|----------------|----------------|----------------|------|
| 81300408 | OL-7/8     | 32,5           | 25,0           | 11,4           | 2,00 |
| 81300413 | OL-13      | 57,0           | 40,0           | 17,5           | 5,30 |
| 81300410 | OL-10      | 43,7           | 31,5           | 13,9           | 3,15 |