

LIFTING SHACKLE USAR

8130-22



Product info For permanent connection.

Forged, straight shackle with spesification US RR-C-271. Delivered galvanized with painted screws - red pin - in straight design. Marking: Maximum load. Product info2

Type Lifting products

Safety factor 6:1

Product group 505

| Part no. | Dimension mm A | Dimension mm B | Dimension mm C | Dimension mm D | |
|----------|----------------|----------------|----------------|----------------|-------|
| 81302222 | 22,0 | 32,0 | 60,0 | 19,0 | 4,75 |
| 81302210 | 10,0 | 13,0 | 27,0 | 7,0 | 0,75 |
| 81302225 | 25,0 | 36,0 | 71,0 | 22,0 | 6,50 |
| 81302211 | 11,0 | 16,0 | 31,0 | 10,0 | 1,00 |
| 81302235 | 35,0 | 52,0 | 100,0 | 32,0 | 12,00 |
| 81302213 | 13,0 | 18,0 | 37,0 | 11,0 | 1,50 |
| 81302219 | 19,0 | 27,0 | 51,0 | 16,0 | 3,25 |
| 81302241 | 41,0 | 60,0 | 124,0 | 38,0 | 17,00 |
| 81302216 | 16,0 | 21,0 | 41,0 | 13,0 | 2,00 |
| 81302229 | 29,0 | 43,0 | 81,0 | 25,0 | 8,50 |
| 81302251 | 51,0 | 73,0 | 146,0 | 44,0 | 25,00 |
| 81302232 | 32,0 | 46,0 | 90,0 | 29,0 | 9,50 |
| 81302208 | 8,0 | 12,0 | 25,0 | 7,0 | 0,50 |
| 81302238 | 38,0 | 57,0 | 113,0 | 35,0 | 13,50 |