


## STUCCHI MULTICONNECT

5SGR3



|                      |              |
|----------------------|--------------|
| <b>Product info</b>  | 3 gates      |
| <b>Product info2</b> | GR type      |
| <b>Product group</b> | 520          |
| <b>Type</b>          | Hydraulic    |
| <b>Manufacturer</b>  | Multiconnect |

### Applications and characteristics

This multi-connect fitting can be used on all types of applications when there is a need to change multi-lined tools, on for example snow ploughs, excavators and cranes. Quick: Connecting and disconnection 2 to 10 hydraulic lines in one instant. Can also be connected during working pressure. Versatile: Can be used for both hydraulic and electrical applications. Environmentally friendly: Drip-free fittings minimizes leakage and prevents dirt from entering the system. Safety: Precludes faulty connections.

| Part no.    | Thread   | Description                      | WP plate | WP fitting |
|-------------|----------|----------------------------------|----------|------------|
| 5SGR391000F | 3/8" BSP | GR3-9 3x9 fixed                  | 66.5     | 35         |
| 5SGR391000M | 3/8" BSP | GR3-9 3x9 mobile                 | 66.5     | 35         |
| 5SGR391001F | 1/2" BSP | GR3-13 3x9 fixed                 | 66.5     | 33         |
| 5SGR391001M | 1/2" BSP | GR3-13 3x9 mobile                | 66.5     | 33         |
| 5S815606008 | -        | Protection cover for GR3-9 fixed | -        | -          |
| 5S815606009 | -        | Parking station for GR3-9 mobile | -        | -          |