

# HYDROSCAND T1111

1031-01



<b>Product group</b>	110
<b>Inner tube</b>	Seamless polyester elastomer
<b>Cover</b>	Oil, weather and abrasion resistant polyurethane
<b>Temperature min. °C</b>	-40
<b>Temperature max. °C</b>	+100
<b>Media</b>	Oil, Water, Welding
<b>Reinforcement</b>	One braid of steel wire
<b>Safety factor</b>	1:4
<b>Applications and characteristics</b>	The hose is well suitable for high pressure hydraulics, as well as pressure washers. The hose is also suited for high pressure gas applications, but then needs to be pin-pricked. Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. NOTE! Air and water max +70.
<b>Design</b>	Black cover
<b>Ferrule</b>	4200-28-xx

## Other



Part no.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
10310103	5	3/16"	9.7	30	36	0.12
10310104	6,50	1/4"	11.7	40	31	0.15
10310105	8	5/16"	13.2	55	25	0.19
10310106	10	3/8"	16.5	65	22,50	0.22
10310108	13	1/2"	18.8	85	19	0.29
10310110	16	5/8"	22	115	14	0.33
10310112	19	3/4"	25.8	145	11,50	0.43
10310116	25	1"	33	180	9,50	0.62