

HYDROSCAND T1112, TWIN

1032-0X



| | |
|---|---|
| Product group | 110 |
| Inner tube | Seamless polyester elastomer |
| Cover | Oil, weather and abrasion resistant polyurethane |
| Temperature min. °C | -40 |
| Temperature max. °C | +100 |
| Media | Oil, Water, Welding |
| Reinforcement | One braid of steel wire |
| Safety factor | 1:4 |
| Applications and characteristics | The hose is well suitable for high pressure hydraulics. The hose is also suited for high pressure gas applications, but then needs to be pin-pricked. Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. NOTE! Air and water max +70. |
| Design | Weldeed twin, black cover |
| Ferrule | 4200-28-xx |

Other



| Part no. | ID mm | ID inch | OD mm | Bend rad mm | WP MPa | Weight kg/m |
|----------|-------|---------|-------|-------------|--------|-------------|
| 10320303 | 5 | 3/16" | 9.7 | 30 | 36 | 0.24 |
| 10320404 | 6,50 | 1/4" | 11.7 | 40 | 31 | 0.3 |
| 10320505 | 8 | 5/16" | 13.2 | 55 | 25 | 0.38 |
| 10320606 | 10 | 3/8" | 16.5 | 65 | 22,50 | 0.44 |
| 10320808 | 13 | 1/2" | 18.8 | 85 | 19 | 0,58 |
| 10321010 | 16 | 5/8" | 22.0 | 115 | 14 | 0.67 |
| 10321212 | 19 | 3/4" | 25.8 | 145 | 11,50 | 0.89 |
| 10321616 | 25 | 1" | 33 | 180 | 9,50 | 1.24 |