



## HYDROSCAND T1110

1064-01



<b>Product group</b>	120
<b>Inner tube</b>	Seamless polyester elastomer
<b>Cover</b>	Durable oil and weather resistant polyurethane
<b>Temperature min. °C</b>	-40
<b>Temperature max. °C</b>	+100
<b>Media</b>	Oil
<b>Reinforcement</b>	One layer of braided steel wire
<b>Safety factor</b>	1:4
<b>Applications and characteristics</b>	Recommended for high pressure hydraulics on marine and offshore equipment. Due to the inner tube of polyester, the hose will retain its flexibility in low temperatures. NOTE! The hose is NOT pin-pricked. The maximum temperature for air and water is +70.
<b>Ferrule</b>	4200-27-xx, 4200-28-xx

### Other



Part no.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
10640103	5	3/16"	9.7	30	36	0.12
10640104	6,50	1/4"	11.7	40	31	0.15
10640105	8	5/16"	13.2	55	25	0.19
10640106	10	3/8"	16.5	65	22,50	0.22
10640108	13	1/2"	18.8	85	19	0.29
10640110	16	5/8"	22	115	14	0.33
10640112	19	3/4"	25.8	145	11,50	0.43
10640116	25	1"	33	180	9,50	0.62