



KAPPAFLEX 2K CO

1105-10



Product group	100
Inner tube	Synthetic oil resistant rubber
Cover	Durable, weather and oil resistant rubber
Temperature min. °C	-40
Temperature max. °C	+100
Media	Oil
Reinforcement	Two braids of compact steel wire
Safety factor	1:4
Applications and characteristics	Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.
Design	Green label, wrapped
Ferrule	4200-11-xx, 4200-23-xx

Other



Material Codes



Part no.	ID mm	ID inch	OD mm	Bend rad mm	Max length	WP MPa	Length min.	Weight kg/m
11051004	6,50	1/4"	13.4	45	-	45	-	0.29
11051005	8	5/16"	15	60	-	42	-	0.34
11051006	10	3/8"	17.4	70	-	38,50	-	0.44
11051008	13	1/2"	20.6	90	-	34,50	-	0.54
11051010	16	5/8"	23.7	130	-	29	-	0.63
11051012	19	3/4"	27.7	160	-	28	-	0.84
11051016	25	1"	35.6	210	-	20	-	1.14
1105100430	6,50	1/4"	13,4	45	230	45	170	0.29
1105100530	8	5/16"	15,0	60	190	42	130	0,31
1105100630	10	3/8"	17,0	70	160	38,50	110	0,39
1105100830	13	1/2"	20,7	90	110	34,50	75	0,52