

KAPPAFLEX 2K CO ROCK

1105-63



Product group	100
Inner tube	Synthetic oil resistant rubber
Cover	Durable; weather and oil resistant rubber
Temperature min. °C	-50
Temperature max. °C	+100
Media	Oil
Reinforcement	Two braids of compact steel wire
Safety factor	1:4
Applications and characteristics	Ozone resistant hose for applications with high pressures and high abrasion. Well suited for marine applications. Impuls tested up to one million cycles. (1 1/4" to 200 000 cycles). Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/reel and a minimum length of 5 meters per length.
Design	Wrapped, black with green label
Ferrule	4200-11-xx, 4200-23-xx, 4200-31-xx

Other



Material Codes



Part no.	ID mm	ID inch	OD mm	Bend rad mm	Max length	WP MPa	Length min.	Weight kg/m
11056304	6,50	1/4"	13,4	45	-	45	-	0,29
11056305	8	5/16"	15,0	60	-	42	-	0,34
11056306	10	3/8"	17,4	70	-	38,50	-	0,44
11056308	13	1/2"	20,6	90	-	34,50	-	0,54
11056310	16	5/8"	23,6	130	-	29	-	0,63
11056312	19	3/4"	27,7	160	-	28	-	0,84
11056316	25	1"	35,6	210	-	20	-	1,14
11056320	32	1 1/4"	43,5	300	-	17,50	-	1,52
1105630430	6,50	1/4"	13,4	45	230	45	170	0,29
1105630530	8	5/16"	15,0	60	190	42	130	0,34
1105630630	10	3/8"	17,4	70	160	38,50	110	0,44
1105630830	13	1/2"	20,6	90	110	34,50	75	0,54