

AQUASEWER, FLUSHING HOSE THERMOPLAST, 250 BAR

1419-XX



Product group 141

Inner tube Polyethylene(PE)

Cover Polyurethane (PU)

Temperature min. °C -40

Temperature max. °C +60

Media Water

Reinforcement Synthetic textile

Safety factor 1:2,5

Applications and characteristics A hose suitable for high pressure sewage systems. The hose has low weight compared to rubber hoses, which leads to less abrasion and increased flowing speed. The hose sustains 3–4 times more external abrasion compared to a traditional rubber hose. It is delivered pre-assembled with fittings according to demand.

Design Smooth, red

Other



Part no.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Weight kg/m
14190608	13	22.8	75	60	25	0.29
14190808	13	22.8	75	80	25	0.29
14191208	13	22.8	75	120	25	0.29
14190612	19,60	30.3	120	60	25	0.49
14190812	19,60	30.3	120	80	25	0.49
14191212	19,60	30.3	120	120	25	0.49
14190616	25,90	37.9	155	60	25	0.62
14190816	25,90	37.9	155	80	25	0.62
14191216	25,90	37.9	155	120	25	0.62
14191220	32,40	45.3	240	120	25	0.740
14191512	19,60	30.3	120	150	25	0.425
14191516	25,90	37.9	155	150	25	0.580
14191520	32,40	45.3	240	150	25	0.740