

AIR PRESSURE HOSE, PVC

1422-30



Product group	142
Inner tube	PVC
Cover	PVC
Temperature min. °C	-5
Temperature max. °C	+60
Media	Air pressure, Water, Food
Reinforcement	Polyester
Safety factor	3:1
Applications and characteristics	This hose is used for compressed air and for transportation of water. It is especially suitable for indoor use. Not for gasoline use. Food approved.

Other



Part no.	ID mm	OD mm	WP MPa 20°C	Bend rad mm	Length m/coil	WP BAR 20°C	Weight kg/m
14223003	5	11	2.0	25	50	20	0.06
14223004	6,30	12	2.0	30	50	20	0.08
14223005	8	14	1.8	40	50	18	0.10
14223006	10	16	1.8	55	50	18	0.12
14220106	10	16	1.8	55	30	18	0.12
14220206	10	16	1.8	55	100	18	0.12
14223008	12,50	19	1.2	75	50	12	0.16
14220108	12,50	19	1.2	75	30	12	0.16
14220208	12,50	19	1.2	75	100	12	0.16
14223010	16	22	1.0	100	50	10	0.21
14223012	19	26	1.0	120	50	10	0.3
14220112	19	26	1.0	120	30	10	0.3
14223014	22	30	0.8	150	50	8	0.37
14223016	25	33	0.8	175	25/50	8	0.44
14220116	25	33	0.8	175	30	8	0.44
14220316	25	33	0.8	175	50	8	0.44
14223020	32	42	0.8	225	25	8	0.70
14220120	32	42	0.8	225	25	8	0.70
14223024	38	48	0.8	295	25	8	0.82
14220124	38	48	0.8	295	30	8	0.82
14223032	50	62	0.8	415	25	8	1.28