

EXMARIN, EXHAUST GAS / MARINE REFILL HOSE

1434-0X



Product group	143
Inner tube	Oil resistant synthetic rubber (NBR)
Cover	Oil resistant synthetic rubber (NBR/SBR)
Temperature min. °C	-30
Temperature max. °C	+100
Media	Oil
Reinforcement	Synthetic textile with a steel spiral
Safety factor	1:3
Applications and characteristics	The hose is suitable for exhaust gas and refill for boats. It fulfils the requirements of Nordic Boat Standard and the Norsk Veritas according to 94/25EC and ISO 7840A1. This means that it can sustain 2.5 minutes in open fire without leaking. It is also CE branded.

Other



Material Codes



Part no.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Weight kg/m
14340012	19	29	120	40	0,30	0.63
14340016	25	35	150	40	0,30	0.78
14340020	32	42	190	40	0,30	0.94
14340024	38	48	230	40	0,30	1.09
14340025	40	50	240	40	0,30	1.14
14340028	45	55	270	40	0,30	1.27
14340030	45	55	270	40	0,30	1.27
14340032	50	60	300	40	0,30	1.41
14340035	55	65	330	40	0,30	1.53
14340038	55	65	330	40	0,30	1.53
14340040	63,50	73.5	380	40	0,30	1.86
14340048	76	86	460	20	0,30	2.25
14340056	90	100	540	20	0,30	2.67
14340064	102	112	610	20	0,30	3.02
14340080	125	141	880	40	0,60	6.1
14340203	203	224	1400	12	0,50	9.5