

MARITIM HOSE FOR WET EXHAUST SAE J2006

1434-70



Product group	140
Inner tube	Black EPDM
Cover	Black EPDM, corrugated
Temperature min. °C	-30
Temperature max. °C	+120
Media	Ventilation, Water
Reinforcement	Synthetic textile cord with steel spiral
Safety factor	1:3
Applications and characteristics	Marine diesel wet exhaust hose according to SAE J2006 R1 and R2. Extremely resistant to sea water, wet exhaust gases, ozone and UV radiation. Light weight with corrugated rubber cover. The steel spiral combined with the design makes this hose very flexible.
Design	Corrugated, black

Other



Material Codes



Part no.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Weight kg/m
14347020	32	40	48	40	0,40	0.45
14347024	40	50	60	40	0,40	0.69
14347028	45	55	68	40	0,40	0.75
14347032	51	61	78	40	0,40	0.85
14347035	57	67	86	40	0,30	0.95
14347039	60	70	90	40	0,30	1
14347040	65	73	95	40	0,30	1.1
14347048	76	87	115	40	0,30	1.25
14347056	90	101	135	40	0,20	1.68
14347064	102	112	155	20	0,20	2.42
14347069	110	122	167	20	0,20	2.9
14347080	127	139	190	20	0,20	3.32
14347096	152	165	230	20	0,20	5.03
14347203	203	218	305	20	0,20	8.56