

## BUSHMASTER, CHEMICAL HOSE, XLPE, 10 BAR

1450-00



|                                         |                                                                                                                                                                                                  |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product group</b>                    | 140                                                                                                                                                                                              |
| <b>Inner tube</b>                       | XLPE                                                                                                                                                                                             |
| <b>Cover</b>                            | EPDM                                                                                                                                                                                             |
| <b>Temperature min. °C</b>              | -30                                                                                                                                                                                              |
| <b>Temperature max. °C</b>              | +90                                                                                                                                                                                              |
| <b>Media</b>                            | Chemicals                                                                                                                                                                                        |
| <b>Reinforcement</b>                    | Synthetic textile with a steel spiral                                                                                                                                                            |
| <b>Safety factor</b>                    | 1:4                                                                                                                                                                                              |
| <b>Applications and characteristics</b> | Flexible hose for suction and pressure applications. The hose is suitable for transportation of chemicals within the petrochemical industry. It is resistant to 90% of all industrial chemicals. |
| <b>Design</b>                           | Wrapped, green                                                                                                                                                                                   |

### Other



| Part no. | ID mm | OD mm | Bend rad mm | Vacuum pr Max% | Length m/coil | WP MPa | Weight kg/m |
|----------|-------|-------|-------------|----------------|---------------|--------|-------------|
| 14500012 | 19    | 32    | 140         | 80             | 40            | 1      | 0.82        |
| 14500016 | 25    | 38    | 150         | 80             | 40            | 1      | 0.92        |
| 14500020 | 32    | 46    | 220         | 80             | 40            | 1      | 1.23        |
| 14500024 | 38    | 52    | 270         | 80             | 40            | 1      | 1.41        |
| 14500032 | 51    | 68    | 380         | 80             | 40            | 1      | 2.34        |
| 14500040 | 63,50 | 80    | 430         | 80             | 40            | 1      | 2.81        |
| 14500048 | 76    | 94    | 520         | 80             | 20            | 1      | 3.61        |
| 14500064 | 102   | 121   | 700         | 80             | 20            | 1      | 5,04        |