

## MARBLE, CONCRETE BLAST HOSE, 40 BAR

1464-10



|                                         |                                                                                                                                                                                                                                                                       |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product group</b>                    | 140                                                                                                                                                                                                                                                                   |
| <b>Inner tube</b>                       | Abrasion resistant rubber (NR/BR)                                                                                                                                                                                                                                     |
| <b>Cover</b>                            | Synthetic abrasion and weather resistant rubber (SBR)                                                                                                                                                                                                                 |
| <b>Temperature min. °C</b>              | -40                                                                                                                                                                                                                                                                   |
| <b>Temperature max. °C</b>              | +70                                                                                                                                                                                                                                                                   |
| <b>Media</b>                            | Materials                                                                                                                                                                                                                                                             |
| <b>Reinforcement</b>                    | Synthetic textile                                                                                                                                                                                                                                                     |
| <b>Safety factor</b>                    | 1:3                                                                                                                                                                                                                                                                   |
| <b>Applications and characteristics</b> | A hose suitable for wet-casting of concrete mixtures at mobile or stationary applications. Also excellent to use as transportation hose between pump and nozzle (for pre-mixed concrete). The thick tube prevents kink in the hose and makes the hose easy to handle. |
| <b>Design</b>                           | Wrapped, black                                                                                                                                                                                                                                                        |

### Other



| Part no. | ID mm | OD mm | Bend rad mm | Length m/coil | WP MPa | Weight kg/m |
|----------|-------|-------|-------------|---------------|--------|-------------|
| 14641012 | 19    | 31    | 120         | 61            | 4      | 0.6         |
| 14641016 | 25    | 38    | 160         | 61            | 4      | 0,82        |
| 14641020 | 32    | 46    | 220         | 61            | 4      | 1.08        |
| 14641022 | 35    | 49    | 250         | 61            | 4      | 1.18        |
| 14641024 | 38    | 54    | 300         | 61            | 4      | 1.42        |
| 14641032 | 51    | 68    | 400         | 61            | 4      | 2.02        |
| 14641040 | 63,50 | 85    | 500         | 40            | 4      | 2.94        |
| 14641048 | 76    | 96    | 600         | 40            | 4      | 3.78        |
| 14641064 | 100   | 128   | 750         | 40            | 4      | 6.10        |