

TRANSPARENT SILICON HOSE

1529



Product group	140
Inner tube	Silicon
Cover	Silicon
Temperature min. °C	-50
Temperature max. °C	+200
Media	Air pressure, food and beverage, special, water
Reinforcement	None
Applications and characteristics	Unreinforced silicon hose suitable for air pressure, water, food and beverage and alcohol up to 50 %. The hose resists repeated sterilisation cycles with a maximum temperatur of 240°C, for short periods.

Other



Part no.	ID mm	OD mm	Length m/coil	Weight kg/m
15290115	1	1,5	25	0,0013
15290102	1	2	25	0,003
15290103	1	3	25	0,008
15290203	2	3	25	0,005
15290204	2	4	25	0,012
15290205	2	5	25	0,021
15290304	3	4	25	0,009
15290305	3	5	25	0,016
15290306	3	5	25	0,027
15290406	4	6	25	0,0205
15290407	4	7	25	0,029
15290408	4	8	25	0,049
15290508	5	8	25	0,0385
15290509	5	9	25	0,057
15290510	5	10	25	0,076
15290608	6	8	25	0,0285
15290609	6	9	25	0,046
15290610	6	10	25	0,065
15290612	6	12	25	0,106
15290710	7	10	25	0,042
15290711	7	11	25	0,046
15290810	8	10	25	0,0365
15290811	8	11	25	0,0575

Part no.	ID mm	OD mm	Length m/coil	Weight kg/m
15290812	8	12	25	0,081
15290813	8	13	25	0,106
15290814	8	14	25	0,117
15290912	9	12	25	0,0635
15291014	10	14	25	0,097
15291016	10	16	25	0,1575
15291012	10	12	25	0,0445
15291015	10	15	25	0,1265
15291018	10	18	25	0,19
15291216	12	16	25	0,113
15291318	13	18	25	0,157
15291520	15	20	25	0,175
15291521	15	21	25	0,20
15291523	15	23	25	0,24
15291525	1,50	2,5	25	0,004
15291619	16	19	25	0,115
15291622	16	22	25	0,239
15291625	16	25	25	0,296
15291824	18	24	25	0,252
15291922	19	22	25	0,136
15292025	20	25	25	0,22
15292027	20	27	25	0,24
15292505	2,50	5	25	0,019
15292532	25	32	25	0,30