

LOW-WEIGHT SPIRAL SUCTION HOSE

1552-00



Product group 140

Inner tube PVC

Cover PVC

Temperature min. °C -5

Temperature max. °C +60

Media Food, Water, Ventilation

Reinforcement White PVC spiral

Safety factor 1:3

Applications and characteristics A low-weight PVC hose for suction and pressure applications. The hose is also suitable for powder transportation within agriculture, food industry and gardening. Smooth inner tube. Sustains alcohols beneath 28%.

Design Corrugated, transparent yellow

Other



Part no.	ID mm	OD mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
15520012	20	27.0	80	70	50	0,70	0.28
15520016	25	31.0	100	70	50	0,70	0.36
15520019	30	37.0	120	70	50	0,50	0.41
15520020	32	39.0	128	70	50	0,50	0.44
15520024	38	45.0	152	70	50	0,50	0.52
15520025	40	47.0	160	70	50	0,50	0.54
15520030	45	52.0	200	70	50	0,60	0.78
15520032	50	58.0	200	70	50	0,50	0.77
15520040	65	74.0	260	70	50	0,40	0.99
15520044	70	79	280	70	50	0,40	1.13
15520048	76	85.0	300	70	50	0,40	1.26
15520056	90	100	415	70	25	0,60	1.75
15520064	100	115.0	400	70	25	0,30	1.98
15520069	110	122	440	50	25	0,30	2.25
15520080	127	138.0	690	50	25	0,40	3.65
15520096	152	164	800	50	25	0,30	5.10
15520200	203	217	1250	50	10	0,30	7.85