

EXHAUST HOSE FOR HOT AIR, NEOPRENE, DOUBLE COATED

1561-1X



Product group	140
Inner tube	Neoprene (CR)
Cover	Neoprene (CR)
Temperature min. °C	-35
Temperature max. °C	+135
Media	Ventilation
Reinforcement	Woven fiberglass, steel spiral
Applications and characteristics	A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.
Design	Slightly corrugated, black

Other



Part no.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP BAR	Weight kg/m
15611016	25	14	5.0	4	2.8	0.19
15611020	32	20	5.0	4	2.7	0.28
15611029	44	27	4.0	4	2.6	0.32
15611032	51	31	4.0	4	2.6	0.36
15611040	63	37	3.0	4	2.4	0.49
15611048	76	43	3.0	4	2.1	0.58
15611055	89	50	2.0	4	2.0	0.69
15611064	102	56	2.0	4	1.9	0.77
15611080	127	70	2.0	4	1.4	0.93
15611096	152	82	1.7	4	1.2	1.20
15611180	180	95	1.0	4	1.0	1.43
15611203	203	108	0.7	4	0.7	1.65