

EXHAUST HOSE FOR HOT AIR, SILICONE, SINGLE COATED

1562-0X



Product group	140
Cover	Silicone, single coated
Temperature min. °C	-50
Temperature max. °C	+300
Media	Ventilation
Reinforcement	Woven fiberglass, steel spiral
Applications and characteristics	A hose suitable for transportation of hot seams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.
Design	Slightly corrugated, red-brown

Other



Part no.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP BAR	Weight kg/m
15620016	25	17	5.0	4	1.5	0.12
15620020	32	17	5.0	4	1.5	0.13
15620029	44	26	0.4	4	1.5	0.19
15620032	51	30	4.0	4	1.5	0.25
15620040	63	36	4.0	4	1.3	0.30
15620048	76	42	0.3	4	1.1	0.41
15620055	89	49	3.0	4	1.1	0.50
15620064	102	55	2.0	4	1.1	0.57
15620080	127	69	1.7	4	0.9	0.81
15620096	152	81	1.4	4	0.8	1.05
15620180	180	96	1.0	4	0.6	1.21
15620203	203	107	0.7	4	0.6	1.38
15620254	254	132	0.4	4	0.4	1.65
15620305	305	158	0.3	4	0.1	2.00