

EXHAUST HOSE FOR HOT AIR, SILICONE, DOUBLE COATED

1562-1X



Product group	140
Inner tube	Silicone
Cover	Silicone
Temperature min. °C	-50
Temperature max. °C	+300
Media	Ventilation
Reinforcement	Woven fiberglass, steel spiral
Applications and characteristics	A hose suitable for transportation of hot seams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.
Design	Slightly corrugated, red-brown

Other



Part no.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP BAR	Weight kg/m
15621016	25	18	5.0	4	2.8	0.19
15621020	32	20	5.0	4	2.6	0.28
15621029	44	27	4.0	4	2.6	0.32
15621032	51	31	4.0	4	2.6	0.36
15621040	63	37	3.0	4	2.4	0.49
15621048	76	43	3.0	4	2.1	0.58
15621055	89	50	2.0	4	2.0	0.69
15621064	102	56	2.0	4	1.9	0.71
15621080	127	70	2.0	4	1.4	0.93
15621096	152	82	1.7	4	1.2	1.20
15621180	180	95	1.0	4	1.0	1.43
15621203	203	108	0.7	4	0.7	1.65