

POLYURETHANE HOSE L 0.4

1563-20



Product group	140
Inner tube	Polyurethane (PU)
Cover	Polyurethane (PU)
Temperature min. °C	-40
Temperature max. °C	+90
Media	Materials, Ventilation
Reinforcement	Copper-coloured steel spiral
Applications and characteristics	A very light weighted hose delivered in a "compact"-package. The hose is very durable and suitable for the food and pharmaceutical industries. Areas of usage: Ventilation, pellet burner, oil mist. The hose is resistant to hydrolysis and microbes. Lengths of 10–15 meters are also available on request.
Design	Corrugated, transparent

Other



Part no.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	Weight kg/m
15632020	32	25	16	6	0.16
15632032	51	26	16	6	0.18
15632040	63	32	14	6	0.22
15632048	76	38	10	6	0.30
15632050	82	40	10	6	0.32
15632055	90	45	7	6	0.35
15632064	102	51	7	6	0.41
15632070	110	55	7	6	0.44
15632073	115	57	7	6	0.46
15632080	127	64	7	6	0.50
15632130	130	65	5	6	0.52
15632085	140	70	5	6	0.55
15632096	152	76	5	6	0.60
15632160	160	80	5	6	0.69
15632170	170	85	5	6	0.73
15632180	180	90	5	6	0.77
15632203	203	102	5	6	0.94
15632228	228	115	5	6	1.03
15632254	254	127	2	6	1.12

Part no.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	Weight kg/m
15632300	300	150	2	6	1.30
15632305	305	153	2	6	1.34
15632318	315	158	2	6	1.38
15632325	325	163	2	6	1.42
15632350	350	175	2	6	1.53
15632400	400	200	2	6	1,74
15632408	408	205	2	6	1.79
15632630	630	425	1	6	4.22