

## SIGMA FS3320 - 60 SHORE

1567-95



<b>Product group</b>	140
<b>Inner tube</b>	Black natural-, BR- and SBR-rubber, 60 shore, antistatic
<b>Cover</b>	Black CR-rubber. Oil, sea water and weather resistant. Electrically conductive
<b>Temperature min. °C</b>	-35
<b>Temperature max. °C</b>	+70
<b>Media</b>	Materials
<b>Reinforcement</b>	Textile and steel spiral
<b>Safety factor</b>	3,2:1
<b>Applications and characteristics</b>	<p>The hose is designed for transport of very abrasive materials such as plaster, ore, glass, wood chips, industrial waste, coal and metallic powder. Can be used in a pneumatic and hydraulic operated construction for materials of different nature.</p> <p>Couplings: The hose should only be used with its corresponding couplings and flanges, see article number 5050-80. Seals are found under article number 5050-90. See related products.</p>
<b>Design</b>	Corrugated
<b>Ferrule</b>	5050-80,5050-90

### Other



Part no.	ID mm	OD mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
15679532	51	75	300	90	40	10	3,00
15679548	82	115	350	90	40	10	7,50
15679564	102	133	500	90	40	10	8,00
15679580	127	161	650	90	20	10	12,00
15679596	152	182	750	90	20	10	14,00
156795203	203	241	1750	90	12	10	18,00
156795254	254	292	2000	90	12	10	22,00
156795305	305	348	2500	90	12	10	28,00