

COMP CHEM 700XX

1584-30



| | |
|---|---|
| Product group | 140 |
| Inner tube | Polypropylene, polyethylene and polyester |
| Cover | Abrasion, UV, ozone and weather resistant polyester |
| Temperature min. °C | -40 |
| Temperature max. °C | +100 |
| Media | Special, Chemicals |
| Reinforcement | Outer and inner stainless steel spiral |
| Safety factor | 1:5 |
| Applications and characteristics | This hose is suitable as a chemical hose with a wide resistance range. Can be used both as suction and pressure hose. Applications for the hose is loading and unloading of gas trucks and railroad cars, and also within industries in different processes. COMP CHEM 700 is 100% aromatically resistant. Electric continuity is attained when the two spirals are put towards the hose's fittings. In this way, static electricity is avoided. On request, a special flame resistant version can also be delivered. Supplied in 40m coils. Vacuum = 70% |
| Design | Green |

Other



| Part no. | ID mm | Bend rad mm | Length m/coil | WP MPa | Weight kg/m |
|----------|-------|-------------|---------------|--------|-------------|
| 15843032 | 50 | 125 | 35 | 1,50 | 2 |
| 15843048 | 75 | 175 | 35 | 1,50 | 3.5 |
| 15843064 | 100 | 250 | 35 | 1,50 | 4.5 |